

MILD STEEL CIRCULAR HOLLOW SECTION

Designation		
Outside Diameter D	Thickness t	Mass per metre
mm	mm	kg
21.3	3.2	1.43
26.9	3.2	1.87
33.7	2.6	1.99
33.7	3.2	2.41
33.7	4.0	2.93
42.2	2.6	2.55
42.2	3.2	3.09
42.2	4.0	3.79
48.3	3.2	3.56
48.3	4.0	4.37
48.3	5.0	5.34
60.3	3.2	4.51
60.3	4.0	5.55
60.3	5.0	6.82
76.1	3.2	5.75
76.1	4.0	7.11
76.1	5.0	8.77
88.9	3.2	6.76
88.9	4.0	8.38
88.9	5.0	10.3
114.3	3.6	9.83
114.3	5.0	13.5
114.3	6.3	16.8
139.7	5.0	16.6
139.7	6.3	20.7
139.7	8.0	26.0
139.7	10.0	32.0
168.3	5.0	20.1
168.3	6.3	25.2
168.3	8.0	31.6
168.3	10.0	39.0
193.7	5.4	25.1
193.7	6.3	29.1
193.7	8.0	36.6
193.7	10.0	45.3
193.7	12.5	55.9
193.7	16.0	70.1

MILD STEEL CIRCULAR HOLLOW SECTION

Designation		
Outside Diameter D	Thickness t	Mass per metre
mm	mm	kg
219.1	6.3	33.1
219.1	8.0	41.6
219.1	10.0	51.6
219.1	12.5	63.7
219.1	16.0	80.1
219.1	20.0	98.2
244.5	6.3	37.0
244.5	8.0	46.7
244.5	10.0	57.8
244.5	12.5	71.5
244.5	16.0	90.2
244.5	20.0	111
273	6.3	41.4
273	8.0	52.3
273	10.0	64.9
273	12.5	80.3
273	16.0	101
273	20.0	125
273	25.0	153
323.9	8.0	62.3
323.9	10.0	77.4
323.9	12.5	96.0
323.9	16.0	121
323.9	20.0	150
323.9	25.0	184
355.6	8.0	68.6
355.6	10.0	85.2
355.6	12.5	106
355.6	16.0	134
355.6	20.0	166
355.6	25.0	204
406.4	10.0	97.8
406.4	12.5	121
406.4	16.0	154
406.4	20.0	191
406.4	25.0	235
406.4	32.0	295
457	10.0	110
457	12.5	137
457	16.0	174
457	20.0	216
457	25.0	266
457	32.0	335
457	40.0	411