

MILD STEEL RECTANGULAR HOLLOW SECTION

Designation		
Size D x D	Thickness t	Mass per metre
mm	mm	kg
50 X 30	2.5	2.81
50 X 30	3.0	3.35
50 X 30	3.2	3.66
60 X 40	2.5	3.71
60 X 40	3.0	4.26
60 X 40	4.0	5.72
80 X 40	3.0	5.17
80 X 40	4.0	6.97
90 X 50	3.0	6.08
90 X 50	3.6	7.46
90 X 50	5.0	10.1
100 X 50	3.0	6.53
100 X 50	4.0	8.86
100 X 50	5.0	10.9
100 X 50	6.3	13.4
100 X 60	3.0	6.99
100 X 60	3.6	8.59
100 X 60	5.0	11.7
100 X 60	6.3	14.4
120 X 60	3.6	9.72
120 X 60	5.0	13.3
120 X 60	6.3	16.4
120 X 80	5.0	14.8
120 X 80	6.3	18.4
120 X 80	8.0	22.9
120 X 80	10.0	27.9
150 X 100	5.0	18.7
150 X 100	6.3	23.3
150 X 100	8.0	29.1
150 X 100	10.0	35.7

MILD STEEL RECTANGULAR HOLLOW SECTION

Designation			
Size	D x D	Thickness	t
	mm	mm	kg
160 X 80		5.0	18.0
160 X 80		6.3	22.3
160 X 80		8.0	27.9
160 X 80		10.0	34.2
200 X 100		5.0	22.7
200 X 100		6.3	28.3
200 X 100		8.0	35.4
200 X 100		10.0	43.6
200 X 100		12.5	53.4
200 X 100		16.0	66.4
250 X 150		6.3	38.2
250 X 150		8.0	48.0
250 X 150		10.0	59.3
250 X 150		12.5	73.0
250 X 150		16.0	91.5
300 X 200		6.3	48.1
300 X 200		8.0	60.5
300 X 200		10.0	75.0
300 X 200		12.5	92.6
300 X 200		16.0	117
400 X 200		10.0	90.7
400 X 200		12.5	112
400 X 200		16.0	142
450 X 250		10.0	106
450 X 250		12.5	132
450 X 250		16.0	167